

WPM9435


P-Channel Enhancement Mode MOSFET

www.willsemi.com

Description


The WPM9435 is the P-Channel logic enhancement mode power field effect transistors are produced using high cell density, DMOS trench technology.

This high density process is especially tailored to minimize on-state resistance. These devices are particularly suited for low voltage application, notebook computer power management and other battery powered circuits where high-side switching.



Features

- -30V/-5A,RDS(ON)= 36mΩ@VGS=- 10V
- -30V/-4A,RDS(ON)= 53mΩ@VGS=-4.5V
- Super high density cell design for extremely low RDS (ON)
- Exceptional on-resistance and maximum DC current capability
- SOP – 8P package design



Application

- Power Management in Note book
- Portable Equipment
- Battery Powered System
- DC/DC Converter
- Load Switch

WPM9435
YYWW

YYWW = Date Code
WPM9435 = Specific Device Code

Order information

Part Number	Part Number	Shipping
WPM9435-8/TR	SOP-8P	2500Tape&Reel

PIN DESCRIPTION

Pin	Symbol	Description
1	S	Source
2	S	Source
3	S	Source
4	G	Gate
5	D	Drain
6	D	Drain
7	D	Drain
8	D	Drain

Absolute Maximum Ratings (TA=25 unless otherwise specified)

Parameter	Symbol			Value	Units		
V _{DS}	Drain-Source voltage			-30	V		
V _{GS}	Gate-Source Voltage			±20	V		
I _D	Continuous Drain Current	Steady-State	TA=25°C	-5.5	A		
		Steady-State	TA=70°C	-4.4			
I _{DM}	Pulse Drain Current			-25	A		
P _D	Power Dissipation	TA=25°C		2.0	W		
		TA=70°C		1.2			
T _J	Operating Junction Temperature Range			-55~150	°C		
T _{stg}	Storage Temperature Range						
R _{θJA}	Thermal Resistance-Junction to Ambient			62.5	°C/W		

Electrical Characteristics


(TA=25°C Unless otherwise noted)

Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
Static						
Drain-Source Breakdown Voltage	V(BR)DSS	V _{GS} =0V, I _D =-250uA	-30			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =-250uA	-1.0	-2.0	-3.0	
Gate Leakage Current	I _{GSS}	V _{DS} =0V, V _{GS} =±20V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =-24V, V _{GS} =0V			-1	uA
		V _{DS} =-24V, V _{GS} =0V T _J =85°C			-10	
On-State Drain Current	I _{D(on)}	V _{DS} = -5V, V _{GS} =-4.5V	-10			A
Drain-Source On-Resistance	R _{D(on)}	V _{GS} =-10V, I _D =-5.0A		0.036	0.046	Ω
		V _{GS} =-4.5V, I _D =-4.0A		0.053	0.066	
Forward Transconductance	g _{fs}	V _{DS} =- 5V, I _D =-5A		8		S
Diode Forward Voltage	V _{SD}	I _S =-1.3A, V _{GS} =0V		-0.79	-1.5	V


Dynamic

Total Gate Charge	Q_g	V _{DSD} =-15V, V _{GGS} =-10V I _D = -3.5A	10	18	nC
Gate-Source Charge	Q_{gs}		1.6		
Gate-Drain Charge	Q_{gd}		3.0		
Input Capacitance	C_{iss}	V _{DSD} =-15V, V _{GGS} =0V f=1MHz	710		pF
Output Capacitance	C_{oss}		115		
Reverse Transfer Capacitance	C_{rss}		100		
Turn-On Time	t _{d(on)}	V _{VDD} =-15V, R _L =15Ω I _D =-1.0A, V _{GEN} =-10V R _G =6Ω		8	18
	t _r			8	18
Turn-Off Time	t _{d(off)}			25	50
	t _f			25	35





Typical Performance Characteristics








Drain Current VS Drain-Source voltage




Drain Current vs ON Resistance


Gate-Source Voltage vs ON Resistance

Drain Current VS Gate-Source Voltage

Drain Current VS Source-Drain Current

On-Resistance vs. Junction


Gate-Charge Characteristics

Capacitance Characteristics

Maximum Forward Biased Safe Operating Area (Note E)

Single Pulse Power Rating Junction-to-Ambient (Note E)

Normalized Maximum Transient Thermal Impedance

Packaging Information

SOP-8P Package Outline Dimension



SYMBOLS	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	1.47	1.60	1.73	0.058	0.063	0.068
A1	0.10	—	0.25	0.004	—	0.010
A2	—	1.45	—	—	0.057	—
b	0.33	0.41	0.51	0.013	0.016	0.020
C	0.19	0.20	0.25	0.0075	0.008	0.0098
D	4.80	4.85	4.95	0.189	0.191	0.195
E	5.80	6.00	6.20	0.228	0.236	0.244
E1	3.80	3.90	4.00	0.150	0.154	0.157
e	—	1.27	—	—	0.050	—
L	0.38	0.71	1.27	0.015	0.028	0.050
\triangle_y	—	—	0.076	—	—	0.003
θ	0°	—	8°	0°	—	8°